



FLOWLUB 2000

Special lubricant for fiber cable and microduct installation.

Great improvement of blowing length

It is a waterbased product with high lubricating effect. It greatly reduces friction and static electricity. Reduces resistance to a minimum.

Easy to apply

The lubrication spreads evenly on the cable surface/ inner wall of the duct. It leaves a very thin film of lubricant and does not make a glue effect.

Low cost

The lubrication is very concentrated, meaning it is very economical to use.

RECOMMENDED QUANTITY PER 1,000 M:

Duct diameter OD	Quantity of FlowLUB 2000
20-30 mm.....	60 ml
30-40 mm.....	70 ml
40-50 mm.....	100 ml

Sharp turns, loops or long blowing lengths will increase the recommended quantity required.

PRODUCT USE

Cable and duct prelubrication.

Shake the bottle before use and apply the lubricant in the duct. Place a suitable sponge in the duct and prelubricate the duct with high pressure air.

SPECIFICATIONS

Item No.:	101-30541
Aspect.....	White liquid tiny viscosity
Odour.....	None
Viscosity.....	120 sec. 4 mm Ford cup at 20°C
Gravity.....	1.030 +/- 0.03 gr/cm ³
PH value.....	7.5 +/- 0.5
Inflammability.....	Non flammable
Temperature.....	From - 5°C to + 70°C
Biodegradability.....	Biodegradable
Toxic.....	Non-toxic





FLOWLUB 5000

Special lubricant for fiber cable and micro cable installation.

Great improvement of blowing length

It is a waterbased product with high lubricating effect. It greatly reduces friction and static electricity.

Easy to apply

The lubrication spreads evenly on the cable surface/ inner wall of the duct. It leaves a very thin film of lubricant and does not make a glue effect.

Low cost

The lubrication is very concentrated, meaning it is very economical to use.

Winter Grade

Available in a special winter version that can handle temperatures down to -10°C/ 14°F.

PRODUCT USE

Cable and duct prelubrication.

Shake the bottle before use and apply the lubricant in the duct. Place a suitable sponge in the duct and prelubricate the duct with high pressure air.

RECOMMENDED QUANTITY PER 1,000 M:

Duct diameter OD	Quantity of FlowLUB 5000
4 mm.....	5 ml = 30 cm full duct
8 mm.....	10 ml = 20 cm full duct
12 mm.....	15 ml = 15 cm full duct

Sharp turns, loops or long blowing lengths will increase the recommended quantity required.

SPECIFICATIONS

Item No.:	101-30531
Aspect.....	White liquid tiny viscosity
Odour.....	Characteristic
Viscosity.....	30 sec. 4 mm Ford cup at 20°C
Gravity.....	1.030 +/- 0.03 gr/cm ³
PH value.....	7.5 +/- 0.5
Inflammability.....	Non flammable
Temperature.....	From 0°C to + 70°C
Biodegradability.....	Biodegradable
Toxic.....	Non-toxic

